

FLETCHER GRANITE CO., LLC

SHORT FORM CSI-FORMATTED SPECIFICATIONS FOR FURNISHING DIMENSIONAL GRANITE

1.01 WORK INCLUDED

A. Provide all equipment and materials, and do all work necessary to furnish fully fabricated granite as required for the completion of all granite work as indicated on the contract drawings and as specified.

1.02 SUBMITTALS

A. SHOP DRAWINGS: Cutting and setting drawings of granite pieces specified herein shall be submitted. Drawings shall indicate sizes, dimensions, layout, finishes, arrangements and provisions for bedding, bonding, jointing, anchoring, cutouts and holes, and other necessary details for reception of other work.

B. SAMPLES: Submit samples of each granite type and finish to show texture, finish and anticipated range of color to be supplied.

C. TEST DATA: Provide test data from independent testing agency for all granite furnished under this Section indicating compliance with the National Building Granite Quarries Association, Inc. (NBGQA) guidelines.

1.03 QUALITY ASSURANCE

A. SOURCE: Granite shall be supplied by a source approved by the Architect. All granite shall be obtained from quarries having capacity and facilities to meet specified requirements.

B. Granite shall be free of cracks, seams, starts or other defects which may impair its strength, durability or appearance. Color, texture and finish shall be within the range of samples approved by the Architect.

C. Granite shall conform to the requirements of ASTM C 615, Architectural Grade and National Building Granite Quarries Association, Inc. "Specifications for Architectural Granite" (NBGQA Specifications)

1.04 DELIVERY, HANDLING AND STORAGE

A. Granite shall be carefully packed and banded by the supplier for shipment. Following shipping, granite shall be stored on wood skids or pallets, covered with nonstaining waterproof membrane and protected from weather. Skids shall be placed and stacked in such a manner as to evenly distribute the weight of the granite materials and to prevent damage to granite pieces. Granite materials shall be stored in such a manner as to allow air to circulate around the material. Granite shall not be permitted to be in direct contact with the ground any time during storage.

B. Granite shall be carefully handled to prevent chipping, breakage, soiling, or other damage. Pinch or wrecking bars shall not be used without protecting the edges with wood or other rigid materials. Granite units shall be lifted with widebelt type slings wherever possible. Wire rope or ropes containing tar or other substances which might cause staining or damage to granite finish will not be permitted.

2.01 GRANITE SUPPLIER

A. Acceptable Source of Granite:

1. Granite shall be supplied by:

Fletcher Granite Co., LLC.,
524 Groton Road,

Westford, Massachusetts 01863;

Telephone (978) 2514031; (800) 2538168; Fax (978) 2511151



2.02 GRANITE

A. Granite Type: Granite shall be equal to the following:

Select Granite types from the following Fletcher Granite Co., LLC granites

GRANITE NAME	QUARRY LOCATION
Addison Black	Addison, Maine
Chelmsford Grey	Westford, Massachusetts
Deer Isle™	Stonington, Maine
Englishman's Bay	Jonesboro, Maine
Jonesboro Red	Jonesboro, Maine
Kitledge Grey	Milford, New Hampshire
Mason	Mason, New Hampshire
Madison	Madison, New Hampshire
Milford Pink	Hopkinton, Massachusetts
Silver Cloud Imperial™	Conyers, Georgia
Tapestry	Milford, New Hampshire

B. Finish: As selected by the Architect.

C. Sizes: As indicated on the Drawings.

D. Fabrication: Fabricate in accordance with tolerances specified in NBGQA Specifications

